

Fabrication and Installation Guide



Thank you for interest in the **StyleLite Waterproof** product range.

This document provides a comprehensive set of technical specifications,
as well as answering common questions about machining, fabrication, installation, and care.

For further information contact us at info@egrdecor.com.au
or contact your nearest StyleLite distributor. For more information, please visit our website.


Contents

Overview	3
Quality Features	3
StyleLite Waterproof Face Panels	3
StyleLite Waterproof Carcass Panels	3
Applications	3
Important Information	3
Warranty	3
TruColour Technology	4
StyleLite Waterproof – Installation & Fabrication Top Tips	4
Unsuitable Applications	4
Guaranteed Quality	4
Storage and Handling	4
Fabrication	5

Overview

StyleLite Waterproof is a high-performance, water-resistant panel solution featuring a durable Weatherproof Composite Core (WCC) and StyleLite TruMatte acrylic surfaces, bonded with advanced PUR reactive hotmelt technology. It is ideal for interior spaces in flood-prone or high-moisture areas such as kitchens, bathrooms, laundries, utility rooms, and mudrooms. The StyleLite TruMatte surface includes TruColor multi-layer UV technology, delivering a premium look and feel with superior durability and performance.

Quality Features



Weatherproof



UV-Protected




Easy to work



Easy to clean



No Fingerprints



Vertical applications

StyleLite Waterproof Face Panels

Smooth, modern matte finish with scratch resistance and anti-fingerprint surface for luxurious look.

Substrate	Finished Panel Size	Application	Weight	Finish
Weatherproof Composite Core (WCC)	2400x1200x18mm	Cabinet doors, face panels, and drawer fronts	13kg/m2	StyleLite TruMatte

StyleLite Waterproof Carcass Panels

Matte textured ABS/acrylic surface with a uniform and consistent look.

Substrate	Finished Panel Size	Application	Weight	Finish
Weatherproof Composite Core (WCC)	2400x1200x16mm	Cabinet carcass, kickboards, base frames and drawer bases panels	12kg/m2	Matte textured


Applications



Flood Prone Areas




Bathrooms




Laundries




Vanities




Mudrooms




Wine Rooms



Fitness



Kickboards



Age Care / Medical

Important Information


- Fabrication and installation must comply with AS/NZS 4386 standard and relevant guidelines in this document.
- EGR DECOR is not liable for improper fabrication or installation of StyleLex products.
- It is the installer's responsibility to ensure the product's suitability for the intended application.

Warranty

- StyleLite Waterproof panels include a limited 7-year warranty.
- StyleLite edgebanding include a limited 1-year warranty.

TruColour Technology

TruColor features a unique combination of clear and coloured UV barrier layers that are fused together during manufacture using a sophisticated multilayer die and triple extrusion process



StyleLite Waterproof – Installation & Fabrication Top Tips

- Install only in undercover indoor areas, away from direct sunlight
- Store panels flat, horizontal, and fully supported at all times
- Panels can be cut and drilled using the same tools as MDF and other wood-based materials.
- Compatible with all standard hardware and hinge systems. Use 5 mm Euro screws for best results.
- Single door panels should be no more than 600 mm wide to ensure strength and stability.
- Fixing points must be placed at intervals of 300 mm or less to provide proper support.
- Pre-drill and countersink are strongly recommended for stronger joints.
- For carcass construction, use screws 51 mm or longer to maintain frame strength.
- Avoid cut-outs or openings on panels; if required, reinforce to reduce warping or twisting.
- Edgebanding is suitable with both EVA and PUR adhesives.
- Do not use as routed panels where the core is exposed, as this may cause bowing.
- Clean surfaces gently — avoid harsh chemicals, solvents, or abrasives.
- Always refer to full StyleLite technical documents and warranty conditions for complete details.

Unsuitable Applications


- StyleLite Waterproof panels are not intended for structural applications.
- StyleLite Waterproof panels are not suitable for outdoor areas.
- StyleLite Waterproof panels are combustible materials

Guaranteed Quality

- StyleLite Waterproof panels comply with the relevant sections of AS/NZS4386.
- StyleLite Waterproof panels is manufactured in Australia at EGR's ISO 9001-accredited facilities.
- StyleLite Waterproof panels is designed to withstand full water submersion under ambient conditions for up to 30 days with no noticeable change

Storage and Handling

- Always handle panels carefully with at least two people to prevent breakage or damage.
- Lift panels during loading and unloading; never drag or slide them.
- Store panels in a clean, dry, and well-ventilated area.
- Keep panels stored flat, horizontally, and fully supported at all times.
- Never transport or store panels in direct sunlight
- Place panel packs on four evenly spaced bearers on a level, hard, and dry surface.
- When stacking multiple packs, ensure gluts/bearers are properly aligned for stability.
- Use protective cover boards on both the top and bottom of packs.
- Follow correct storage practices to avoid bowing or warping.



Fabrication

Overview


- StyleLite Waterproof panels can be cut and drilled with standard woodworking tools.
- Always run a small trial to confirm the best speed and settings.
- Rough edges may result from friction, poor support, or worn/inadequate tools.
- Adjust cutting to avoid edge strands, which can affect edgebanding quality.
- Keep machines well-ventilated and use dust extraction during processing.
- Control heat during cutting to prevent edge melting or surface marks.
- Inspect all panels for defects on arrival, before cutting or fabrication.

Cutting

- StyleLite Waterproof panels can be cut using standard carbide or diamond tools.
- A small-diameter, 2-flute (wing) tool is recommended for best performance.
- Set compression routers to 16,000–18,000 RPM.
- Other cutting parameters are the same as MDF.

Hinge Recommendation

- Always test hinge drilling on a sample panel to confirm depth and backset.
- StyleLite Waterproof door panels must use the correct number of hinges, spaced no more than 300 mm apart.




Saw Cutting

- Panels can be cut using standard settings on panel saws or beam saws.
- A sharp carbide-tipped triple chip grind (TCG) blade is recommended.
- Use blades with 3–5 teeth per centimetre for smooth, clean results.
- Maintain a low cutting height (15–30 mm) for best performance.
- Operate at standard or lower RPM to reduce heat build-up.
- Keep a steady, continuous feed speed — avoid stopping during the cut.
- A scoring blade should be used on panel saws to prevent edge chipping.

Drilling

- Use carbide or diamond drill bits with a 110°–130° point angle for clean holes.
- Drill at slow to medium speed with light pressure to prevent heat or cracks.
- Always place the panel on a firm backing to stop vibration and breakout.
- Keep the drill perpendicular for accuracy and to avoid laminate damage.
- Make holes slightly larger than fasteners to allow expansion and prevent stress cracks.



StyleLite Waterproof Panel – Size & Design Requirements

- Single door panels must not exceed 600 mm in width.
 - Cut-outs or openings are not recommended.
- Reinforce when necessary to minimise warping or twisting.

General Recommendation

- Fully compatible with standard hardware and hinge systems.
- Use 5 mm Euro screws for strong and secure installation.
- For doors and front panels, ensure fixing points are no more than 300 mm apart.
- If drawer system fasteners are spaced wider than 300 mm, add extra fixing points. A support bracket should be fitted beneath the bottom drawer panel.
- Do not over-tighten screws or apply force (e.g., hammering) during assembly, as this may damage the panel.

Carcass Construction Recommendation

- Use screws at least 51 mm long to build a strong and stable cabinet frame.
- Always pre-drill pilot holes and countersink before fastening to avoid splitting.
- Do not over-tighten screws or apply force (e.g., hammering) during assembly, as this may damage the panel.
- Position the first screw at least 35 mm from each edge to prevent splitting.
- For standard-sized cabinets, space screws 150–200 mm apart on centre.
- For larger cabinets, reduce screw spacing to 100–150 mm apart for extra reinforcement.

Cleaning During Fabrication

- Clean spills immediately to prevent stains or damage.
- During fabrication, wipe gently with a microfiber cloth and a lightly dampen a microfiber cloth.
- Test all new cleaning products on a hidden area before use
- Do not use abrasives, strong solvents, or harsh chemicals. Never use the following products:
 - ✗ Acidic cleaners e.g. vinegar, rust removers, or limescale removers
 - ✗ Alkaline cleaners e.g. bleach, oven cleaners, baking soda.
 - ✗ Ammonia-based cleaners e.g. window and glass cleaners
 - ✗ Strong solvents e.g. acetone, isopropyl alcohol (IPA) or methylated spirits
 - ✗ Abrasive cleaners e.g. scouring pads, rough sponges, or gritty cleaners like CIF
 - ✗ ABS edgetape cleaner.

Edge Finishing

- StyleLite edgeband is compatible with EVA and PUR adhesives.
- Use PUR adhesive for harsh or high-moisture environments.
- Run trials to set the best machine settings for each job.
- Adjust trimming tools and scrapers to avoid surface damage or lips
- Use white glue on white panels and clear glue on coloured panels.
- Only use cleaning agents approved by the adhesive supplier — always test on a small sample first.
- If glue overrun or surface contamination occurs, wipe gently with a microfiber cloth dampened with white spirit (mineral turpentine).
- ✗ Never use ABS edgeband cleaners on StyleLite.



StyleLite[®] by **EGR DECOR**

Waterproof Cabinetry Fabrication and Installation Guide

EGR Decor

45 Machinery St, Darra, Brisbane
Queensland 4076, Australia

www.stylelite.net

info@egrdecor.com

+61 7 3718 1100

1. EGR expressly disclaims any representations or warranties of any kind, whether express or implied, as to the accuracy, currency, completeness and/or the merchantability or fitness for a particular purpose of any information contained in or provided via this documentation and/or any service or product described or promoted in this document. 2. It is the customer's responsibility to thoroughly examine the product using a qualified person, to determine whether it is suitable for the application it was purchased for. 3. The receiver of our products is fully responsible to check and to take into account possible third party's patent rights, as well as the existing laws in the country of installation prior to installing our product. 4. No liability may be derived from these images or statements nor from our free technical advice. 5. EGR reserves the right to change, add or remove colours or product without notice. 6. EGR Decor and EGR are registered trademarks. 7. Images and colours should be used as a guide only. 8. Ten Year Indoor Warranty: The EGR Decor warranties cover faulty materials for the periods specified on the relevant product warranty documents.

The EGR Decor warranties commence from the date of sale by EGR, they are not transferable and are subject to the terms, conditions and exclusions contained within those warranties.

@ Copyright 2024 / Patent Pending Oakmoore Pty Ltd trading as EGR